



LAUNDRY

WALL ROLLER AND WALL
FLATWORK IRONERS



WIDE RANGE OF COMPACT MACHINES
FOR ALL TYPE OF BUSINESS





INDEX

WIDE RANGE OF COMPACT MACHINES
FOR ALL TYPE OF BUSINESS

04

A PERFECT AND INNOVATIVE SOLUTION
FOR THE IRONING OR DRYING,
IRONING AND FOLDING OF THE FLATWORK

06

WALL ROLLER IRONERS.
USER-FRIENDLY,
RELIABLE, ROBUST AND NOT EXPENSIVE

08

WALL FLATWORK IRONERS

11

TECHNICAL DATA

14



Wall roller ironers



Wall flatwork ironers
roll 35

Wall flatwork ironers
roll 50

WIDE RANGE OF
COMPACT MACHINES
FOR ALL TYPE OF BUSINESS.

FAGOR INDUSTRIAL presents a wide range of mural flatwork ironers, a perfect and innovative **solution for the ironing or drying, ironing and folding of the flatwork**, for all type of customers.

New flatwork ironers, models with lengthfold, crossfold and stacker and the choice of rear or front delivery, offer great flexibility to adapt to all type of needs and uses.

Fagor ironers are conceived to offer the **best performance** and **productivity** with noticeable energetic efficiency and time-saving. Their easy operation makes **the maintenance costs almost non-existent**.

The ironing quality from Fagor machines is well known by the users and considered one of the strong points.

A PERFECT AND INNOVATIVE SOLUTION FOR THE IRONING OR DRYING, IRONING AND FOLDING OF THE FLATWORK

WALL ROLLER IRONERS

WALL FLATWORK IRONERS Ø 14" (325 mm)

ROLL DIAMETRE (inches) / (mm)	HEATING	ROLL LENGTH ((inches) / (mm))	
		63" / 1600	79" / 2000
14" / 325	ELECTRIC, GAS	PS-35/160 MP	PS-35/200 MP

WALL FLATWORK IRONERS Ø 20" (500 mm)

ROLL DIAMETRE (inches) / (mm)	HEATING	ROLL LENGTH (inches) / (mm)		
		79" / 2000	105" / 2600	130" / 3300
20" / 500	ELECTRIC, GAS	PS-50/200 MP	PS-50//260 MP	PS-50//330 MP





WALL ROLLER IRONERS

USER-FRIENDLY,
RELIABLE, ROBUST AND
NOT EXPENSIVE

Specially designed for the restaurant and small production area.

The new range of mural ironers is the ideal choice for those laundries which do not have a big output but where the investment point matters. Its easy use makes them perfect to iron the flatwork from restaurants, small hotels, youth hostels, etc.



Electrically heated, there are two versions, diameter 7" (180mm) and 10" (250mm). The linen needs the previous drying in a tumbler to get the moisture of 20-25% which will provide the optimum ironing results. Their simple mechanism makes them reliable and long-lasting, being the cheapest option for the smaller laundries.

These machines are small in dimensions and mural, so they can be placed in a reduced space, with hardly installation as they do not have air exhaust or connections except the electric supply.

FEATURES

- Front feed and return.
- Panels in stainless steel and painted steel.
- Roll dimensions: from 39" (1.000 mm) to 56" (1.400 mm) wide and diameter from 7" (180mm) to 10"(250 mm).
- Electronic microprocessor to control the temperature.
- Electric heating.
- Roll covered in polyester and cotton felt.

OPTIONS

- Possibility to work at hiegher temperatures, up to 374 °F (190 °C), with NOMEX padding.

WALL FLATWORK IRONERS

NEW CONCEPT IN IMPROVING AND SPEEDING UP THE FLATWORK DRYING AND IRONING PROCESS

- | | | | |
|----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>01. MAINTENANCE CARE</p> <p>A simple but reliable design with easy-to-access mechanical parts and top quality components.</p> | <p>02. STAINLESS STEEL DESIGN</p> <p>Panels in Stainless Steel which provides better quality and an elegant look.</p> | <p>03. INVERTER</p> <p>Frequency control in all models.</p> | <p>04. MP ELECTRONIC CONTROL</p> <p>Easy to use and intuitive, the electronic control allows the selection of the speed and temperature of the roll for an optimal ironing.</p> |
| <p>05. HIGH-TECH ROLL</p> <p>High performance steel ironing roll.</p> | <p>06. RADIANT BURNER</p> <p>For a more efficient ironing.</p> | | |

OPTIONALS :

- | | |
|------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <p>07. CHROMED ROLL</p> <p>Optional chromed roll for a better performance and longer life.</p> | <p>08. SMART SYSTEM</p> <p>Humidity control which adapts the roll speed depending on the moisture of the flatwork.</p> |
|------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|

STAINLESS FINISH
Panels in stainless steel and lacquered steel.



WALL FLATWORK IRONERS

NEW CONCEPT IN IMPROVING AND SPEEDING UP THE FLATWORK DRYING AND IRONING PROCESS

The range of flatwork ironers with rolls from 8" (200mm), 14" (325mm) and 20" (500mm) is perfect for those small and medium sized laundries which need an optimum ironing quality with minimum operation and maintenance costs.



Wall flatwork ironers roll 35



Wall flatwork ironers roll 50

The ironing output (between 22lb/hr (10 kg/hr) and 265 lb/hr (120 kg/h), depending on model) and the heating types (electric, gas, steam) makes them flexible to adapt to the different needs of the customers.

Their renovated design is now more ergonomic and reduces the drying and ironing times of the flat linen to the minimum. Their easy operation makes the maintenance costs almost non-existent.

The possibility to work exclusively from the front for both the feeding and collection of the linen, offers space saving for its installation and operation.

WALL FLATWORK IRONERS

Ø 8" (200mm)
PSE 20/140 MP

PSE 20/140 MP Is the smallest model which can dry-iron the flatwork, ideal for reduced spaces.



FEATURES

- Front feed and return.
- Roll dimensions 55" (1.400mm). wide, and diameter 8" (200 mm).
- Frequency Inverter for the ironing speed control.
- Panels in painted steel.
- Nomex feeding and ironing belts for an easy operation, top ironing quality and long-lasting belts.
- Electronic microprocessor (speed and temperature control).
- Electric heating.



WALL FLATWORK IRONERS

Ø 14" (325mm)

Fagor flatwork ironers Ø 14" (325mm) is ideal for those small and medium sized laundries which need an optimum ironing quality with minimum operation and maintenance costs.



OPTIONS



Drying



Ironing



The ironing output between 22 and 88 lb/h (10 and 40 kg/h) depending on the model) and their heating types (electric and steam) makes them flexible to adapt to the different customer needs.

FEATURES

- Front feed and return.
- Roll dimensions from 55" 1400mm to 79" 2000m m. wide, and diameter 14" (325 mm).
- Frequency Inverter for the ironing speed control.

- Panels in Stainless Steel and painted steel.
- Powerful exhaust system.
- Nomex feeding and ironing belts for an easy Operation, top ironing quality and long-lasting belts.
- Electronic microprocessor (speed and temperature control).
- Electric and gas heating.
- New gas model with radiant burner (25% production increase).

OPTIONS

- Chromed cylinder, better performance and longer life.



WALL FLATWORK IRONERS

Ø 20" (500mm)

This range has been updated with new roll dimensions to offer a higher performance and versatility, with roll lengths of 79" (2.000mm) 106" (2.600mm and 130" (3.300 mm) diameter 20" (500 mm).).



OPTIONS



Drying



Ironing



FEATURES

- Front feed and return.
- Roll dimensions: width 79" (2.000mm) 106" (2.600mm). and 130" (3.300 mm) diameter 20" (500 mm).
- Frequency Inverter for the ironing speed control.
- Panels in Stainless Steel and painted steel.
- Powerful exhaust system.

- Nomex feeding and ironing belts for an easy Operation, top ironing quality and long-lasting belts.
- Electronic microprocessor (speed and temperature control).
- Electric, gas and steam heating.
- New gas model with radiant burner (25% production increase).

OPTIONS

- Smart system, moisture control. Only Ø 20" (500mm)
- Chromed cylinder, better performance and longer life.
- Reverse roll rotation.



FAGOR COMMERCIAL, Inc.

13105 NW 47th Avenue, Opa Locka, FL, 33054
T. (+1) 305 779 0170 | 866 GO FAGOR

us.marketing@onneragroup.com

www.fagorcommercial.com



ISO 9001

